

MODEL		KAJ0100	KAK0100	KAL0100	KAT0100	KAL0150	KAT0150
NET OIL PRESSURE		N/A	N/A	N/A	N/A	N/A	N/A
CYLINDERS		2	2	2	2	2	2
BORE		1-9/16	1-11/16	1-7/8	1-7/8	1-7/8	1-7/8
STROKE		1-5/16	15/16	15/16	1-5/32	15/16	1-5/32
DISPLACEMENT CFH		218.4	255	313	389	313	389
OIL GRADE		150	150	150	150	150	150
OIL CHARGE OZ.		24	24	24	24	24	24
NET WEIGHT		89	89	89	89	89	94
RATED BTUH @ SST LISTED	R12 45°F						
	R12 0°F	3400	4070	5300		4800	6360
	R12 -20°F				3630		
	R22 45°F						
	R22 25°F						
	R502 -20°F	3150				4300	
MOTOR SIZE HP		1	1	1	1	1-1/2	1-1/2
ELECTRICAL DATA							
115 -1- 60	LRA	85.5	85.5	85.5	85.5	---	---
	RLA	12.4	11.4	10.9	12.4	---	---
	MCC	17.3	15.9	15.2	17.3	---	---
230 -1- 60	LRA	33.5	33.5	33.5	33.5	44.0	44.0
	RLA	5.4	5.4	5.1	5.5	5.6	6.1
	MCC	7.2	7.5	7.1	7.7	7.6	8.5
208-230 -3- 60	LRA	25.0	25.0	25.0	25.0	35.5	35.5
	RLA	3.4	3.3	3.3	3.9	5.4	5.0
	MCC	4.8	4.6	4.6	5.5	7.1	7.0
460 -3- 60	LRA	15.0	15.0	15.0	15.0	18.2	18.2
	RLA	2.1	1.9	1.8	2.1	2.9	2.9
	MCC	2.8	2.7	2.5	2.9	3.6	4.0

Conditions: 130° Condensing Temperature, 0° Subcooling, 65° RGT,