

MODEL	4RA-0750	4RA1000	4RE1000	4RH1500	4RK1500	4RL1500	4RA2000	4RE2000	4RH2500	4RK2500	4RJ3000	4RR3000	
CAPACITY CONTROL	NO	NO	YES	NO	YES	NO	NO	ONE	NO	ONE	NO	ONE	
NET OIL PRESSURE	20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60	20-60	
CYLINDERS	4	4	4	4	4	4	4	4	4	4	4	4	
BORE	2-1/2	2-1/2	2-1/2	2-11/16	2-11/16	2-11/16	2-1/2	2-1/2	2-11/16	2-11/16	2-15/16	2-15/16	
STROKE	2	2	2	2-3/16	2-3/16	2-3/16	2	2	2-3/16	2-3/16	2-3/16	2-3/16	
DISPLACEMENT CFH	2380	2380	2380	3020	3020	3020	2380	2380	3020	3020	3603	3603	
OIL GRADE	150	150	150	150	150	150	150	150	150	150	152/234	152/234	
OIL CHARGE OZ.	168	168	168	136	136	136	136	136	152	152	152	152	
NET WEIGHT	364	369	374	407	412	407	394	403	415	427	470	470	
RATED BTUH @ SST LISTED X 1000	R12 45°F		106.0	106.0	148.9	148.9							
	R12 0°F		39.7	39.7	50.3	50.3							
	R12 -20°F	20.8											
	R22 45°F						186.1	186.1	231.2	231.2	270.0	270.0	
	R22 25°F						118.9	118.9	72.4		84.5		
	R502 -20°F		37.4	37.4			78.0	66.2					
MOTOR SIZE HP	7-1/2	10	10	15	15	15	20	20	25	25	30	30	
ELECTRICAL DATA													
208-230 -3- 60	LRA	172	240.0	240.0	278.0	278.0	278.0	308.0	308.0	428.0	428.0	470.0	470.0
	RLA	27.6	54.8	54.8	63.3	63.3	62.6	71.4	71.4	88.5	88.5	102.0	102.0
	MCC	38.6	76.8	76.8	88.2	88.2	87.7	100.0	100.0	121.5	124.0	135.0	135.0
460 -3- 60	LRA	86.0	120.0	120.0	139.0	139.0	139.0	154.0	154.0	214.0	214.0	235.0	235.0
	RLA	13.8	27.4	27.4	31.5	31.5	31.3	35.7	35.7	44.3	44.3	51.0	51.0
	MCC	19.3	38.4	38.4	44.1	44.1	43.9	50.0	50.0	60.8	62.0	67.5	67.5
575 -3- 60	LRA	65.0	106.0	106.0	113.0	113.0	113.0	135.0	135.0	160.0	160.0	200.0	200.0
	RLA	11.9	19.8	19.8	24.2	24.2	24.2	29.2	29.2	34.8	34.8	42.2	42.2
	MCC												

Conditions: 130° Condensing Temperature, 0° Subcooling, 65° RGT,