

| | | | | | | | |
|--------------|---|---|---|---|---|---|---|
| MODEL | 2 | F | 5 | B | 8 | 8 | N |
| DIGIT | 1 | 2 | 3 | 4 | 5 | 6 | 7 |

REFRIGERANT TYPE
 1 = R12 (HERMETIC ONLY)
 2 = R22 (HERMETIC ONLY)
 3 = OPEN DRIVE

| MODEL (TONS) | | | | |
|--------------|------|------|------|------|
| CYL.. | E | | F | |
| | R-12 | R-22 | R-12 | R-22 |
| 3 | - | - | 10 | 15 |
| 4 | 30 | 50 | 12.5 | 20 |
| 5 | 40 | 60 | 15 | 25 |
| 6 | 50 | 75 | 20 | 30 |
| 8 | 60 | 100 | 25 | 40 |

SPEED 5 = 1800 RPM

| | |
|---|------------------------------------|
| N | SOLENOID UNLOADING |
| W | 100% UNLOADING (100% UNLOAD START) |
| R | RIGHT HAND |
| L | LOW LIFT VALVES |
| Z | REMOTE MOUNT ELECT. SOL. UNLOAD |
| Y | 100% UNLOAD w/ REMOTE SOLENOID |
| X | NON UNLOADING COMPRESSOR |

| ELECTRICAL CHARACTERISTICS | |
|----------------------------|-----------------------------|
| 0 | OPEN |
| 1 | 460-3-60 SIX LEAD |
| 2 | 575-3-60 SIX LEAD |
| 7 | 440-3-60 SIX LEAD |
| 8 | 200/230/460/-3-60 NINE LEAD |
| 9 | 480-3-60 SIX LEAD |

NUMBER OF CYLINDERS 3, 4, 5, 6 OR 8

DESIGN SEQUENCE A, B, C, D