

MODEL 1F5(A-B)		3	4	5	6	8	MODEL 1F5(C-D)		4	5	6	8	
A & B DESIGN		HERMETIC R-12					C & D DESIGN		HERMETIC R-12				
NET OIL PRESSURE		75	75	75	75	75	NET OIL PRESSURE		75	75	75	75	
CYLINDERS		3	4	5	6	8	CYLINDERS		4	5	6	8	
BORE		2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	BORE		2-3/4	2-3/4	2-3/4	2-3/4	
STROKE		2	2	2	2	2	STROKE		2	2	2	2	
DISPLACEMENT CFM		36.1	48.1	60.2	72.2	96.2	DISPLACEMENT CFM		48.1	60.2	72.2	96.2	
OIL GRADE		300	300	300	300	300	OIL GRADE		300	300	300	300	
OIL CHARGE PINTS		13-1/2	18	19	19	20-1/2	OIL CHARGE PINTS		18	19	19	20-1/2	
NET WEIGHT		790	710	790	810	922	NET WEIGHT		626	694	690	776	
RATED TONS	R-12	10	12-1/2	15	20	25	RATED TONS	R-12	12-1/2	15	20	25	
MOTOR SIZE HP		10	12-1/2	15	20	25	MOTOR SIZE HP		12-1/2	15	20	25	
LARGE MOTOR BARREL						SMALL MOTOR BARREL							
ELECTRICAL DATA		A/C AIR COOLED - W/C WATER COOLED					ELECTRICAL DATA		A/C AIR COOLED - W/C WATER COOLED				
230-3-60	LRA	157	200	220	290	365	230-3-60	LRA	200	230	304	382	
	A/C RLA	32.5	47	56	72	88		A/C RLA	47	50	65	80	
	W/C RLA	29	42	50	64	80		W/C RLA	42	45	58	72	
460-3-60	LRA	79	100	110	145	182	460-3-60	LRA	100	115	152	191	
	A/C RLA	16.5	23.5	28	36	44		A/C RLA	23.5	25	33	40	
	W/C RLA	14.5	21	25	32	40		W/C RLA	21	22	29	36	
575-3-60	LRA	57		84	111	140	575-3-60	LRA		88	111	140	
	A/C RLA	13.8		21.4	27	34		A/C RLA		21	27	34	
	W/C RLA	12.8		19.2	24	31		W/C RLA		19	24	31	